

■高位熱効率/低位熱効率 一覧表

株式会社ノーリツ

業務用ガス給湯器

					都市ガス13A ※2		LPG（プロパン） ※2	
製品名	設置	エコジョーズ (潜熱回収型)	給湯最大出力		高位熱効率	低位熱効率	高位熱効率	低位熱効率
			kW	kcal/h	%	%	%	%
GQ-C5042WZ	屋外	○	87.2	75,000	95%	105%	95%	103%
GQ-C5032WZ			87.2	75,000	95%	105%	95%	103%
GQ-C5032WZ-H			87.2	75,000	95%	105%	95%	103%
GQ-C5032WZQ			87.2	75,000	95%	105%	95%	103%
GQ-C3222WZ-1			55.8	48,000	95%	105%	95%	103%
GQ-C3223WZ			55.8	48,000	95%	105%	95%	103%
GQ-C2434WZ-C			41.9	36,000	95%	105%	95%	103%
GQ-C2034WZ-C			34.9	30,000	95%	105%	95%	103%
GQ-C1634WZ-C			27.9	24,000	95%	105%	95%	103%
GQ-5011WZ-3		—	87.2	75,000	78%	86%	78%	84%
GQ-5011WZQ-3			87.2	75,000	78%	86%	78%	84%
GQ-3211WZ-3			55.8	48,000	80%	89%	80%	設定なし
GQ-3211WZQ-3			55.8	48,000	80%	89%	80%	設定なし
GQ-3210WZ-3			55.8	48,000	80%	設定なし	80%	87%
GQ-3210WZQ-3			55.8	48,000	80%	設定なし	80%	87%
GQ-2421WZ-3			41.9	36,000	80%	89%	80%	設定なし
GQ-2420WZ-3			41.9	36,000	80%	設定なし	80%	87%
GQ-1621WZ-3			27.9	24,000	80%	89%	80%	設定なし
GQ-1620WZ-3			27.9	24,000	80%	設定なし	80%	87%
GQT-C2401SAWZ		○	41.9	36,000	95%	105%	95%	103%
GQ-C5052WZD-F ※1	屋内	○	87.2	75,000	95%	105%	95%	103%
GQ-C2422WZD-F			41.9	36,000	95%	105%	95%	103%
GQ-C1622WZD-F			27.9	24,000	95%	105%	95%	103%
GQ-C2422WZD-FH-1			41.9	36,000	95%	105%	95%	103%
GQ-C1622WZD-FH-1			27.9	24,000	95%	105%	95%	103%
GQ-5021WZD-F		—	87.2	75,000	80%	89%	80%	87%
GQ-5021WZQD-F			87.2	75,000	80%	89%	80%	87%
GQ-3210WZ-FF-3			55.8	48,000	80%	89%	80%	87%
GQ-3210WZQ-FF-3			55.8	48,000	80%	89%	80%	87%
GQ-2420WZD-F-3			41.9	36,000	80%	89%	80%	87%
GQ-1620WZ-FFA-3			27.9	24,000	80%	89%	80%	87%
GQ-1620WZD-F-3			27.9	24,000	80%	89%	80%	87%

業務用石油給湯機

					灯油 ※2	
製品名	設置	エコフィール (潜熱回収型)	給湯最大出力		高位熱効率	低位熱効率
			kW	kcal/h	%	%
OQB-C4701WZS	屋外	○	46.5	40,000	96%	103%
OQB-407WZ		—	46.5	40,000	84%	90%
OQB-C4701WZFF	屋内	○	46.5	40,000	96%	103%
OQB-407WZFF		—	46.5	40,000	84%	90%
OQB-407WZFF			46.5	40,000	84%	90%

※1 2026年9月発売予定

※2 都市ガス13A : 高位発熱量45.0MJ/m³N 低位発熱量40.6MJ/m³N

LPG(プロパン) : 高位発熱量101.4MJ/m³N 低位発熱量93.7MJ/m³N

灯油 : 高位発熱量46.5MJ/kg 低位発熱量43.5MJ/kg で計算

「(公財) 日本小型貫流ボイラー協会 ボイラー性能表示基準値」 (2024年版)